

Gamelan

Páčka na skladanie
ERX.44P-M5X16-C3

Na spajanie podstav

<http://www.motedis.com/shop/Slot-profiles-accessories/Accessoires-20-I-Typ-slot-5/Automatic-Fastener-I-Type-slot-5::2504.html>

<http://leehite.org/Chimes.htm>

Hliníková trubka 28mm/2mm

Nota	Frekvencia	Dĺžka	Závesný bod
C4	261,60	807,4	181,0
C#/Db	277,20	785,2	176,0
D#/Eb	311,10	740,8	166,1
G	392,00	659,9	147,9
G#/Ab	415,30	640,8	143,7
C5	523,30	571,1	128,0
C#/Db	554,40	555,2	124,5
D#/Eb	622,30	523,5	117,4
G	784,00	466,4	104,6
G#/Ab	830,60	453,7	101,7
C6	1 046,50	404,5	90,7
C#/Db	1 108,70	391,8	87,8
D#/Eb	1 244,50	371,2	83,2
G	1 568,00	329,9	74,0
G#/Ab	1 661,20	320,4	71,8

From:

<http://knowledge.lom.audio/> - LOM knowledge base

Permanent link:

<http://knowledge.lom.audio/gamelan?rev=1483744103>

Last update: **2017/01/07 00:08**

