

Gamelan

Páčka na skladanie
ERX.44P-M5X16-C3

Na spajanie podstav

<http://www.motedis.com/shop/Slot-profiles-accessories/Accessoires-20-I-Typ-slot-5/Automatic-Fastener-I-Type-slot-5::2504.html>

<http://leehite.org/Chimes.htm>

Hliníková trubka 28mm/2mm

Nota	Frekvencia	Dĺžka	Závesný bod
C4	261,60	807,4	181,0
C#/Db	277,20	785,2	176,0
D#/Eb	311,10	740,8	166,1
G	392,00	659,9	147,9
G#/Ab	415,30	640,8	143,7
C5	523,30	571,1	128,0
C#/Db	554,40	555,2	124,5
D#/Eb	622,30	523,5	117,4
G	784,00	466,4	104,6
G#/Ab	830,60	453,7	101,7
C6	1 046,50	404,5	90,7
C#/Db	1 108,70	391,8	87,8
D#/Eb	1 244,50	371,2	83,2
G	1 568,00	329,9	74,0
G#/Ab	1 661,20	320,4	71,8

Nižšie položený

Nota	Frekvencia	Dĺžka	Závesný bod
C4	253,60	820,1	
C#/Db	269,20	796,3	
D#/Eb	303,10	750,3	
G	384,00	666,2	
G#/Ab	407,30	647,2	
C5	515,30	575,8	
C#/Db	546,40	558,4	
D#/Eb	614,30	526,6	
G	776,00	469,5	
G#/Ab	822,60	455,3	
C6	1 038,50	406,1	
C#/Db	1 100,70	393,4	
D#/Eb	1 236,50	371,2	

Nota	Frekvencia	Dĺžka	Závesný bod
G	1 560,00	331,5	
G#/Ab	1 653,20	322,0	

From:

<http://knowledge.lom.audio/> - **LOM knowledge base**

Permanent link:

<http://knowledge.lom.audio/gamelan?rev=1511124890>

Last update: **2017/11/19 21:54**

