

| Model | Uši Pro | Ucho Pro | Uši |
|-------------------------------------|--|---|------------------------------|
| Description | Matched phantom powered, pre-polarized condenser microphones | Phantom powered, pre-polarized condenser microphone | |
| Operating voltage | 24-48V | 28-48V | 2-10V |
| Cable | 2 x 1.5 m with 2.5 mm diameter | 1.5 m with 2.5 mm diameter | 1.5 m with 2.5 mm diameter |
| Maximum input pressure level | ~122 dB SPL | ~122 dB SPL | ~122 dB SPL |
| Sensitivity | -28 dB at 1kHz (± 3 dB) | -28 dB at 1kHz (± 3 dB) | -28 dB at 1kHz (± 3 dB) |
| Self-noise | ~14 dBA | ~14 dBA | ~14 dBA |
| Output | 2x XLR-3M balanced, transformer-less, floating | XLR-3M balanced, transformer-less, floating | 3.5mm (1/8") jack |
| Output impedance | 30-50 Ω | 30-50 Ω | 2.4 k Ω |
| Power consumption | ~3mA per pin | ~3mA per pin | ~700 μ A |

From:

<http://knowledge.lom.audio/> - **LOM knowledge base**

Permanent link:

http://knowledge.lom.audio/manuals/usi_comparison?rev=1518466398

Last update: **2018/02/12 21:13**

