

Model	Uši Pro	Ucho Pro	Uši
<b>Description</b>	Matched phantom powered, pre-polarized condenser microphones	Phantom powered, pre-polarized condenser microphone	Matched stereo pair of pre-polarized condenser microphones
<b>Operating voltage</b>	24-48V (P48 phantom power)	28-48V (P48 phantom power)	2-10V (plug-in power)
<b>Cable</b>	2 x 1.5 m with 2.5 mm diameter	1.5 m with 2.5 mm diameter	1.5 m with 2.5 mm diameter
<b>Maximum input pressure level</b>	~122 dB SPL	~122 dB SPL	~122 dB SPL
<b>Sensitivity</b>	-28 dB at 1kHz ( $\pm 3$ dB)	-28 dB at 1kHz ( $\pm 3$ dB)	-28 dB at 1kHz ( $\pm 3$ dB)
<b>Self-noise</b>	~14 dBA	~14 dBA	~14 dBA
<b>Output</b>	2x XLR-3M balanced, transformer-less, floating	XLR-3M balanced, transformer-less, floating	3.5mm (1/8") jack
<b>Output impedance</b>	30-50 $\Omega$	30-50 $\Omega$	2.4 k $\Omega$
<b>Power consumption</b>	~3mA per pin per channel	~3mA per pin	~700 $\mu$ A per channel

From:

<http://knowledge.lom.audio/> - **LOM knowledge base**

Permanent link:

[http://knowledge.lom.audio/manuals/usi\\_comparison?rev=1518466524](http://knowledge.lom.audio/manuals/usi_comparison?rev=1518466524)

Last update: **2018/02/12 21:15**

